

TopWorx™ GO™ Switch Model 7L 5/8" Dual LED Proximity Sensor

2.5mm sensing | 316L Stainless Steel Enclosure | Single Pole Double Throw (SPDT)



Applications:

- Manual valves
- Linear valves
- Rack and pinion actuators
- Gates
- Restricted access door/panel indication

Features & benefits:

Polarity Insensitive, i.no need to specify NPN or PNP:

- Easily adaptable to NPN or PNP circuits

Simple contact arrangement

- Can be wired as a Normally Open (Form A), Normally Closed (Form B) or Normally Open/ Normally Closed (Form C)

Bright Dual LED indication

- Large LED domes stand out and are visible from long distances

Certified for use in Hazardous Locations

- cULus Cl I, Div 2 Groups A-D; Cl II, Div 2 Groups E-G; Cl III



Submersible

- IP68 rated at 1 meter for 24 hours

Stainless Steel Sensing Face

- Offers higher durability to physically abusive environments.
- Withstands external pressure up to 140 bar (2000 psi)

Quick Delivery

- Available through the GO™ Switch Express shipping program which allows for fast part replacement and greater availability

Specifications:

Sensing Distance		
Ferrous Metal	AMS7	AMS4
2.5mm	5mm	9mm

Voltage Rating	
AC	DC
120V AC	24VDC

Vibration Resistance: 10-55Hz, 1.5mm double amplitude

Shock Resistance: 1000m/s²

Switch Frequency: 10Hz

For more information:
www.topworx.com

TOPWORX™


EMERSON™